




DATASHEET
Single-Phase Hybrid/AC Inverter
H1-3.0 / 3.7 / 4.6 / 5.0 / 6.0-E-G2
AC1-3.0 / 3.7 / 4.6 / 5.0 / 6.0-E-G2



H1&AC1(G2) HYBRID/AC INVERTER

Harness the power of the sun day and night with the ground-breaking range of Hybrid & AC inverters from Fox ESS.

Full of advanced features and compatible with our very own range of high-voltage batteries, the hybrid range from Fox ESS. It is a new class of Inverter.



Fox ESS storage solutions are available with advanced and intuitive app based remote control and monitoring functionality.



Easy Installation

Flexible configuration, plug and play set-up, built-in fuse protection.



High Voltage

Includes high-voltage batteries for maximum round-trip efficiency.



IP65 Rated

Engineered to last with maximum flexibility. Suitable for outdoor installation.



Remote Monitoring

Monitor your system remotely via smartphone app or web portal.



up to
6kW
charge/
discharge

REFINED – POWERFUL – FLEXIBLE

BATTERY EXPANSION EASY UPGRADE



Expand your system easily by simply adding additional batteries. There are six battery size options, and Max. seven batteries can be installed in series, providing up to 33.24kWh of storage capacity.

For more about the FOX range, visit:

WWW.FOX-ESS.COM



TECHNICAL SPECIFICATIONS

Model	H1-3.0-E-G2 AC1-3.0-E-G2	H1-3.7-E-G2 AC1-3.7-E-G2	H1-4.6-E-G2 AC1-4.6-E-G2	H1-5.0-E-G2 AC1-5.0-E-G2	H1-6.0-E-G2 AC1-6.0-E-G2
INPUT PV (ONLY FOR HYBRID)					
Max. Input Power [W]	4500 A:2250 B:2250	5500 A:2750 B:2750	6900 A:3450 B:3450	7500 A:3750 B:3750	9000 A:4500 B:4500
Max. Input Voltage [V]			600		
Start-up Input Voltage [V]			75		
Rated Input Voltage [V]			360		
MPPT Operating Voltage Range [V]			80 ~ 550		
Max. Input Current [A]			16 / 16		
Max. Short-circuit Current [A]			20 / 20		
No. of Independent MPP Trackers			2		
No. of Strings per MPP Tracker			1		
BATTERY CONNECTION					
Battery Type			Lithium Battery (LFP)		
Battery Voltage [V]			80 ~ 480		
Max. Charge/Discharge Current [A]			40		
Communication Interface			CAN(communicate with inverter, upgrade BMS)		
AC INPUT AND OUTPUT (GRID)					
Max. AC Input Power [VA]	6000	7680	9200	10000	12000
Max. AC Input Current (per phase) [A]	27.3	34.9	41.8	45.5	54.5
Rated Output Power [W]	3000	3680	4600	5000	6000
Max. Output Apparent Power [VA]	3300	4048/3680 ¹	5060	5500	6600
Rated Output Current (per phase) [A]	13.6	16.7/16 ¹	20.9	22.7	27.3
Rated Output Current (per phase) [A](For AUS)	13.0	16.0	20.0	21.7	26.1
Max. Output Current [A]	15.0	18.4	23.0	25.0	30.0
Rated Grid Voltage [V]			220/230/240		
Rated Grid Frequency [Hz]			50/60		
Power Factor			1 (Adjustable from 0.8 leading to 0.8 lagging)		
THDi [%]			<3 @rated power		
EPS OUTPUT (WITH BATTERY)					
Max. Output Apparent Power [VA]	3000	3680	4600	5000	6000
Peak Output Apparent Power (60s) [VA]	3600	4400	5500	6000	7200
Max. Current (per phase) [A]	13.6	16.7	20.9	22.7	27.3
Rated Output Voltage [V]			220/230/240		
Rated Output Frequency [Hz]			50/60		
Power Factor			1 (Adjustable from 0.8 leading to 0.8 lagging)		
THDv (linear Load) [%]			<2 @rated power		
Parallel operation [PCS]			10		
Switch time [ms]			<20		
EFFICIENCY					
Euro Efficiency [%]	95.26	95.70	96.23	96.30	96.33
Max. Efficiency [%]	97.01	97.08	97.04	97.08	97.08
Max. Battery Charge Efficiency (PV to BAT) (@full load) [%]			98.50		
Max. Battery Discharge Efficiency (BAT to AC) (@full load) [%]			97.00		
PROTECTION					
Insulation Monitoring			YES		
Residual Current Monitoring			YES		
DC Reverse Polarity Protection			YES		
Anti-islanding Protection			YES		
AC Short-circuit Protection			YES		
AC Overcurrent/Overvoltage Protection			YES		
DC Switch			YES		
Battery Wack-up Function			YES		
SPD			DC: Type II, /AC: Type III		
AFCI			Optional		
GENERAL DATA					
Dimensions (WxHxD) [mm]			434*418*185		
Weight [kg]			22		
Installation			Wall-Mounted		
Topology			Non-isolated		
Cooling Method			Natural		
Noise Emission [dB]			35		
Max. Operating Altitude [m]			2000		
Operating Temperature Range [°C]			-25 ~ 60		
Humidity (No Condensation) [%]			0 ~ 100		
Ingress protection			IP65		
Standby consumption[W]			< 15		
Monitoring Module			WiFi, LAN(optional) , 4G(optional)		
Communication			RS485, DRM, Ripple Control, USB, CAN		
Display			LCD, App, Website		
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)					
Safety			EN 62109-1, EN 62109-2		
Grid Regulation			AS / NZS 4777.2		

* More technical characteristics are available on demand and customized.

1、 3680 for G98. 2、 4600 for German and Belgium. 3、 5000 for Australia and Belgium.